

Dekor Textil
curtain textile upholstery fabric



Breite/Höhe **ca. 140 cm**
width/height

Gewicht **400 g/m²**
weight

Material **100% PES FR**
material

Pflegeanleitung
care instructions



englisch dekori
 vienna

Schwer brennbar **Ja/yes**
flame retardant
 EN 1021 1+2
 EN 13773
 ÖNORM B3825
 ÖNORM A3800
 DIN 4102 - B1
 BS5867 - TYPE B+C
 CLASSE UNO
 IMO - FTP PART 7
 IMO - FTP PART 8

Lichtechtheit **5**
fastness to light
 EN ISO 105-B02

Reibechtheit (trocken) **4**
fastness to rubbing (dry)
 EN ISO 105-X12

Reibechtheit (nass) **3-4**
fastness to rubbing (wet)
 EN ISO 105-X12

Pilling **4**
pilling
 EN ISO 12945-2

Scheuertouren Martindale **80000**
abrasion resistance Martindale
 EN ISO 12947

Schallabsorberklasse **C**
sound absorption class
 EN ISO 11654

Schallabsorptionsgrad **0,70**
noise reduction coefficient : NRC
 ASTM C423

Zugfestigkeit Kette **1000**
tensile strength warp
 EN ISO 13934-1

Zugfestigkeit Schuss **1200**
tensile strength weft
 EN ISO 13934-1

Vorbehaltlich Druck- und Satzfehler. Die Farben der Abbildungen können von der tatsächlichen Produktfarbe abweichen.

Typing and printing errors reserved. The color(s) of the actual product may slightly differ from those shown on this page.

Dekor **Textil**
curtain textile upholstery fabric



Weiterreißfestigkeit Kette **28**
tear strength warp EN ISO 13937-3

Weiterreißfestigkeit Schuss **46**
tear strength weft EN ISO 13937-3

Nahtschiebewiderstand
resistance to seam slippage EN ISO 13936-2

Öko-tex Standard 100 **Ja/yes**
öko-tex Standard 100

Samt/Velours **Ja/yes**
velvet