

Textil
textile upholstery fabric

Dekor
curtain



Breite/Höhe **ca. 140 cm**
width/height

Gewicht **400 g/m²**
weight

Material **100% PES FR**
material

Pflegeanleitung
care instructions



englisch dekori
vienna

Schwer brennbar
flame retardant

Ja/yes

EN 1021 1+2
BS5852 - SOURCES 0+1
EN 13773
ÖNORM B3825
ÖNORM A3800
DIN 4102 - B1
BS5852 - CRIB 5
BS5867 - TYPE B+C
CLASSE UNO
IMO - FTP PART 7
IMO - FTP PART 8

Lichtechtheit **5**
fastness to light

EN ISO 105-B02

Reibechtheit (trocken) **4**
fastness to rubbing (dry)

EN ISO 105-X12

Reibechtheit (nass) **3-4**
fastness to rubbing (wet)

EN ISO 105-X12

Pilling **4**
pilling

EN ISO 12945-2

Scheuertouren Martindale **85000**
abrasion resistance Martindale

EN ISO 12947

Schallabsorberklasse **C**
sound absorption class

EN ISO 11654

Schallabsorptionsgrad **0,70**
noise reduction coefficient : NRC

ASTM C423

Zugfestigkeit Kette **1000N**
tensile strength warp

EN ISO 13934-1

Zugfestigkeit Schuss **1200N**
tensile strength weft

EN ISO 13934-1

Vorbehaltlich Druck- und Satzfehler. Die Farben der Abbildungen können von der tatsächlichen Produktfarbe abweichen.

Typing and printing errors reserved. The color(s) of the actual product may slightly differ from those shown on this page.

Textil

textile upholstery fabric

Dekor

curtain



Weiterreißfestigkeit Kette

tear strength warp

28N

EN ISO 13937-3

Weiterreißfestigkeit Schuss

tear strength weft

46N

EN ISO 13937-3

Nahtschiebewiderstand

resistance to seam slippage

EN ISO 13936-2

Öko-tex Standard 100

öko-tex Standard 100

Ja/yes

Samt/Velours

velvet

Ja/yes