

**Textil**  
textile upholstery fabric

**Dekor**  
curtain



**Breite/Höhe**  
width/height

ca. 150 cm


**Gewicht**  
weight

400 g/m<sup>2</sup>

**Material**  
material

70% WV, 25% PA, 5% AF

**Pflegeanleitung**  
care instructions



A2102/150

**Resteinsprung**  
shrinkage

2-3 %

**Schwer brennbar**  
flame retardant

**Ja/yes**

EN 1021 1+2  
BS5852 - SOURCES 0+1  
EN 13773  
ÖNORM B3825  
ÖNORM A3800  
CLASSE UNO  
IMO - FTP PART 7  
IMO - FTP PART 8

**Lichtechtheit**  
fastness to light

4-5

EN ISO 105-B02

**Reibechtheit (trocken)**  
fastness to rubbing (dry)

4-5

EN ISO 105-X12

**Reibechtheit (nass)**  
fastness to rubbing (wet)

4

EN ISO 105-X12

**Pilling**  
pilling

4-5

EN ISO 12945-2

**Scheuertouren Martindale**  
abrasion resistance Martindale

65000

EN ISO 12947

**Schallabsorberklasse**  
sound absorption class

**A**

EN ISO 11654

**Schallabsorptionsgrad**  
noise reduction coefficient : NRC

0,90

ASTM C423

**Abdunkelung**  
darkening

95 %

EN 14501



Vorbehaltlich Druck- und Satzfehler. Die Farben der Abbildungen können von der tatsächlichen Produktfarbe abweichen.

Typing and printing errors reserved. The color(s) of the actual product may slightly differ from those shown on this page.

## Textil

textile upholstery fabric

## Dekor

curtain



<b>Zugfestigkeit Kette</b> <i>tensile strength warp</i>	<b>511</b> EN ISO 13934-1
<b>Zugfestigkeit Schuss</b> <i>tensile strength weft</i>	<b>301</b> EN ISO 13934-1
<b>Weiterreißfestigkeit Kette</b> <i>tear strength warp</i>	<b>43</b> EN ISO 13937-3
<b>Weiterreißfestigkeit Schuss</b> <i>tear strength weft</i>	<b>28,9</b> EN ISO 13937-3
<b>Nahtschiebewiderstand</b> <i>resistance to seam slippage</i>	<b>3,5/2,8</b> EN ISO 13936-2
<b>Recycelt</b> <i>recycled</i>	<b>Ja/yes</b>
<b>Thermo</b> <i>thermo</i>	<b>Ja/yes</b>