

## Textil

textile upholstery fabric




**Breite/Höhe** **ca. 140 cm**  
width/height

**Gewicht** **400 g/m<sup>2</sup>**  
weight

**Material** **50% PES FR, 37% MAC, 13% CO**  
material

**Pflegeanleitung** **feucht abwischen /**  
care instructions **clean with a damp cloth**



englisch dekor  
vienna

A1805/140

**Schwer brennbar** **Ja/yes**  
flame retardant  
EN 1021 1+2  
ÖNORM B3825  
ÖNORM A3800  
CLASSE UNO  
IMO - FTP PART 8

**Fleckschutz** **Ja/yes**  
stain repellent

**Easy Clean** **Ja/yes**  
easy clean

**Lichtechtheit** **4-5**  
fastness to light  
EN ISO 105-B02

**Reibechtheit (trocken)** **4-5**  
fastness to rubbing (dry)  
EN ISO 105-X12

**Reibechtheit (nass)** **3-4**  
fastness to rubbing (wet)  
EN ISO 105-X12


**Pilling** **4-5**  
pilling  
EN ISO 12945-2

**Scheuertouren Martindale** **50000**  
abrasion resistance Martindale  
EN ISO 12947

**Garntyp** **einfach**  
yarn type *single*

**Bindung** **Leinwand**  
weave *plain*

**Färbemethode** **STÜCKFÄRBER**  
dyeing method



Vorbehaltlich Druck- und Satzfehler. Die Farben der Abbildungen können von der tatsächlichen Produktfarbe abweichen.

Typing and printing errors reserved. The color(s) of the actual product may slightly differ from those shown on this page.

## Textil

*textile upholstery fabric*



<b>Zugfestigkeit Kette</b> <i>tensile strength warp</i>	<b>800</b> EN ISO 13934-1
<b>Zugfestigkeit Schuss</b> <i>tensile strength weft</i>	<b>800</b> EN ISO 13934-1
<b>Weiterreißfestigkeit Kette</b> <i>tear strength warp</i>	<b>40</b> EN ISO 13937-3
<b>Weiterreißfestigkeit Schuss</b> <i>tear strength weft</i>	<b>40</b> EN ISO 13937-3
<b>Nahtschiebewiderstand</b> <i>resistance to seam slippage</i>	<b>4</b> EN ISO 13936-2