

Textil
textile upholstery fabric



Breite/Höhe **ca. 150 cm**
width/height

Gewicht **420 g/m²**
weight

Material **70% WO REC, 30% PES FR**
material

Pflegeanleitung
care instructions



englisch dekor
vienna

A2266/150

Resteinsprung **2-3 %**
shrinkage

Rapportbreite **ca. 6 cm**
repeat width

Schwer brennbar **Ja/yes**
flame retardant

EN 1021 1+2
BS5852 - SOURCES 0+1
EN 13773
ÖNORM B3825
ÖNORM A3800
CLASSE UNO
IMO - FTP PART 7
IMO - FTP PART 8

Lichtechtheit **4-5**
fastness to light

EN ISO 105-B02

Reibechtheit (trocken) **4-5**
fastness to rubbing (dry)

EN ISO 105-X12

Reibechtheit (nass) **4**
fastness to rubbing (wet)

EN ISO 105-X12

Pilling **4-5**
pilling

EN ISO 12945-2

Scheuertouren Martindale **65000**
abrasion resistance Martindale


EN ISO 12947

Schallabsorberklasse **A**
sound absorption class

EN ISO 11654

Schallabsorptionsgrad **0,90**
noise reduction coefficient : NRC

ASTM C423



Vorbehaltlich Druck- und Satzfehler. Die Farben der Abbildungen können von der tatsächlichen Produktfarbe abweichen.

Typing and printing errors reserved. The color(s) of the actual product may slightly differ from those shown on this page.

Textil

textile upholstery fabric



Abdunkelung <i>darkening</i>	95 % EN 14501
Zugfestigkeit Kette <i>tensile strength warp</i>	510 EN ISO 13934-1
Zugfestigkeit Schuss <i>tensile strength weft</i>	300 EN ISO 13934-1
Weiterreißfestigkeit Kette <i>tear strength warp</i>	43 EN ISO 13937-3
Weiterreißfestigkeit Schuss <i>tear strength weft</i>	29 EN ISO 13937-3
Recycelt <i>recycled</i>	Ja/yes
Thermo <i>thermo</i>	Ja/yes