

**Dekor**  
curtain




**Breite/Höhe** **approx. 140 cm**  
*width/height*

**Gewicht** **420 g/m<sup>2</sup>**  
*weight*

**Material** **70% WO REC, 25% PA, 5% AF**  
*material*

**Pflegeanleitung**  
*care instructions*



englisch dekor  
vienna

E3506/140

**Resteinsprung** **2-3 %**  
*shrinkage*

**Rapporthöhe** **approx. 32 cm**  
*repeat height*

**Schwer brennbar** **Ja/yes**  
*flame retardant*  
EN 13773  
ÖNORM A3800  
CLASSE UNO  
IMO - FTP PART 7

**Lichtechtheit** **4-5**  
*fastness to light*  
EN ISO 105-B02

**Reibechtheit (trocken)** **4-5**  
*fastness to rubbing (dry)*  
EN ISO 105-X12

**Reibechtheit (nass)** **4**  
*fastness to rubbing (wet)*  
EN ISO 105-X12


**Pilling** **4-5**  
*pilling*  
EN ISO 12945-2

**Schallabsorberklasse** **A**  
*sound absorption class*  
EN ISO 11654

**Schallabsorptionsgrad** **0,90**  
*noise reduction coefficient : NRC*  
ASTM C423

**Abdunkelung** **95 %**  
*darkening*  
EN 14501

**Zugfestigkeit Kette** **511**  
*tensile strength warp*  
EN ISO 13934-1



Vorbehaltlich Druck- und Satzfehler. Die Farben der Abbildungen können von der tatsächlichen Produktfarbe abweichen.

Typing and printing errors reserved. The color(s) of the actual product may slightly differ from those shown on this page.

**Dekor**  
*curtain*



<b>Zugfestigkeit Schuss</b> <i>tensile strength weft</i>	<b>301</b> EN ISO 13934-1
<b>Weiterreißfestigkeit Kette</b> <i>tear strength warp</i>	<b>43</b> EN ISO 13937-3
<b>Weiterreißfestigkeit Schuss</b> <i>tear strength weft</i>	<b>28,9</b> EN ISO 13937-3
<b>Nahtschiebewiderstand</b> <i>resistance to seam slippage</i>	<b>3,5/2,8</b> EN ISO 13936-2
<b>Recycelt</b> <i>recycled</i>	<b>Ja/yes</b>
<b>Thermo</b> <i>thermo</i>	<b>Ja/yes</b>