

TEST REPORT

2025AU0089

DATE OF RECEPTION

Date Format: dd/MM/yyyy 28/01/2025

DATE TESTS

Starting: 29/01/2025

Ending: 03/02/2025

APPLICANT

ENGLISCH DEKOR HANDELSGMBH & CO KG
SCHEYDGASSE 29
AT-1210 WIEN
Austria

Att. Kim Villaluz

IDENTIFICATION AND DESCRIPTION OF SAMPLES

Reference by AITEX	Reference by customer	AITEX sample description
2025AU0089-S01	TOUCH BASIC	Fabric

TESTS CARRIED OUT

- FURNITURE ASSESSMENT OF THE IGNITABILITY OF UPHOLSTERY FURNITURE.

Tests marked with * are not included within the scope of the ENAC accreditation.

Rev.1 This revision cancels and replaces the previous
Description error





DESCRIPTION OF SAMPLES



Reference by AITEX: 2025AU0089-S01

Reference by customer:

TOUCH BASIC

AITEX sample description:

Tela vinílica color gris claro adherida a un tejido de aspecto aterciopelado color blanco. / *Light grey vinyl fabric adhered to a white velvety-looking fabric.*

Composition provided by the customer:

52 % PU, 8 % Silicona, 40 % Poliéster, con un gramaje de 540 g/m². / *52 % PU, 8 % Silicone, 40 % Polyester, with a weight of 540 g/m².*



RESULTS

FURNITURE ASSESSMENT OF THE IGNITABILITY OF UPHOLSTERY FURNITURE

Standard

EN 1021-1:2014

Reference

2025AU0089-S01

Standard conditioned

24 h (for at least) / (23±2) °C and (50±5) %HR

Starting and time date	Ending and time date
29/01/2025 16:00	03/02/2025 15:30

Ambiental conditions test

20,8 °C / 53,1 %HR.

Speed air

0,08 m/s

SubstrateNon-fire retardant polyurethane foam having density of 20-22 Kg/m³**Test date**

03/02/2025

>>>



Ignition source Smouldering cigarette

- a) Smouldering escalating unsafe
- b) Test assembly consumed
- c) Smoulders specimen extremities
- d) Smoulders through thickness
- e) Smoldering more than an hour
- f) Shows evidence of active smouldering
- g) Cigarettes Self-extinguish
- h) Result: P = Pass | F = Fail.

Specimen	a	b	c	d	e	f	g	h
Specimen 1	NO	NO	NO	NO	NO	NO	NO	P
Specimen 2	NO	NO	NO	NO	NO	NO	NO	P
Specimen 3	NA	NA	NA	NA	NA	NA	NA	NA

NA = No applied

***NOTE:** 3rd cigarette is tested only in self-extinguishing case.

Observations

During the test, there is a moderate emission of grey smoke. The cigarettes have been extinguished at 5 min 30 seconds and 4 min 46 seconds, respectively.

Test uncertainty

± 2.5%

Standard deviations

Observations

The test results relate to the behavior of the test specimens of a product under the particular conditions of the test; they are not intended to be the sole criterion for assessing the potential fire hazard of the product in use.

CRITERIA OF IGNITION PROGRESSIVE SMOULDERING IGNITION
a) Any test assembly that displays escalating combustion behavior so that it is unsafe to continue the test and active extinction is necessary.
b) Any test assembly that smolders until it is largely consumed within the test duration.
c) Any test assembly that smolders to the extremities of the specimen, viz, upper or lower margins, either side or to its full thickness, within the duration of the test.
d) Any test assembly that smolders for more than one hour.
e) Any test assembly that, on final examination, shows evidence of active smoldering.

///

Reference by AITEX	Description	Reference by customer
2025AU0089-S01	Tela vinílica color gris claro adherida a un tejido de aspecto aterciopelado color blanco.	TOUCH BASIC



RESULTS

FURNITURE ASSESSMENT OF THE IGNITABILITY OF UPHOLSTERY FURNITURE

Standard

EN 1021-2:2014

Reference

2025AU0089-S01

Standard conditioned

24 h (for at least) / (23±2) °C and (50±5) %HR

Starting and time date	Ending and time date
29/01/2025 16:00	03/02/2025 15:30

Ambiental conditions test

20,9 °C / 54,6 %HR.

Speed air

0,08 m/s

SubstrateNon-fire retardant polyurethane foam having density of 20-22 Kg/m³**Test date**

03/02/2025

>>>



Ignition source

Butane flames equivalent to match flame

- a) Smouldering escalating unsafe
- b) Test assembly consumed
- c) Smoulders specimen extremities
- d) Smoulders through thickness
- e) Flaming more than 120 s
- f) Result: P = Pass | F = Fail.

Specimen	a	b	c	d	e	f
Specimen 1	NO	NO	NO	NO	NO	P
Specimen 2	NO	NO	NO	NO	NO	P
Specimen 3	NO	NO	NO	NO	NO	P

Observations

During the test, there is a low emission of grey smoke.

Test uncertainty

± 2.5%

Standard deviations

Observations

The test results relate to the behavior of the test specimens of a product under the particular conditions of the test; they are not interested to be the sole criterion for assessing the potential fire hazard of the product in use.

CRITERIA OF IGNITION FLAMING IGNITION
a) Any test assembly that displays escalating combustion behavior so that it is unsafe to continue the test and active extinction is necessary.
b) Any test assembly that smolders until it is largely consumed within the test duration.
c) Any test assembly that smolders to the extremities of the specimen, viz, upper or lower margins, either side or to its full thickness, within the duration of the test.
d) Any flaming which continues for more than 120 s after removal of the burner tube.

///

Reference by AITEX	Description	Reference by customer
2025AU0089-S01	Tela vinílica color gris claro adherida a un tejido de aspecto aterciopelado color blanco.	TOUCH BASIC



Joan Risueño
Head of Fire Behaviour lab.



Date: 12/02/2025 10:47:46
Digitally Signed by: JOAN RISUEÑO CABANES -
NIF: 48605765A

LIABILITY CLAUSES

- 1.- AITEX is liable only for the results of the methods of analysis used, as expressed in the report and referring exclusively to the materials or samples indicated in the same which are in its possession, the professional and legal liability of the Centre being limited to these. Unless otherwise stated, the samples were freely chosen and sent by the applicant.
- 2.- AITEX shall not be liable in any case of misuse of the test materials nor for undue interpretation or use of this document. AITEX laboratories do not carry out sampling.
- 3.- The Offer and / or Order to which the applicant gives approval through signature and seal, constitutes the Legally Executable Agreement in which AITEX is responsible for safeguarding and guaranteeing the absolute confidentiality of the management of all the information obtained or created during the performance of the contracted activities.
- 4.- In the eventuality of discrepancies between reports, a check to settle the same will be carried out in the head offices of AITEX. Also, the applicants undertake to notify AITEX of any complaint received by them as a result of the report, exempting this Centre from all liability if such is not done, the periods of conservation of the samples being taken into account.
- 5.- AITEX will provide at the request of the person concerned, the treatment of complaints procedure. In the event that you want to make it, direct it to: calidad@aitex.es.
- 6.- AITEX is not responsible for the information provided by customers, which is reflected in the Report, and may affect the validity of the results. The information provided by the client is not covered by the scope of ENAC accreditation.
- 7.- AITEX is not responsible for an inadequate state of the sample received that could compromise the validity of the results, expressing such circumstance, in the test reports.
- 8.- AITEX may include in its reports, analyses, results, etc., any other evaluation which it considers necessary, even when it has not been specifically requested.
- 9.- When a Declaration of Conformity is requested, if not indicated otherwise, the decision rule according to ILAC-G8: 2009 will be applied with a security zone of 1U and a Probability of False Acceptance <2.5%.
- 10.- The uncertainties of tests, which are made explicit in the Results Report, have been estimated for a $k = 2$ (95% probability of coverage). If not informed, they are available to the client in AITEX.
- 11.- The original materials and rests of samples, not subject to test, will be retained in AITEX during the twelve months following the issuance of the report, so that any check or claim which, in his case, wanted to make the applicant, should be exercised within the period indicated.
- 12.- This report may only be sent or delivered by hand to the applicant or to a person duly authorised by the same.
- 13.- The results of the tests and the statement of compliance with the specification in this report refer only to the test sample as it has been analyzed / tested and not the sample / item which has taken the test sample.
- 14.- The client must attend at all times, to the dates of the realization of the tests.
- 15.- According to Resolution EA (33) 31, the test reports must include the unique identification of the sample, and any brand or label of the manufacturer may be added. It is not allowed to re-issue test reports of untested sample names (references), they can only be re-issued for error correction or inclusion of omitted data that were already available at the time of the test. The laboratory can not assume responsibility for declaring that the product with the new trade name / trademark is strictly identical to the one originally tested; This responsibility belongs to the client.
- 16.- This report may not be partially reproduced without the written approval of the issuing laboratory.