

TEST REPORT


Report Ref.	LEI25010597A Original		
Date Received	13/01/2025	Date Issued	15/01/2025

Company Name & Address	Englisch Dekor Scheydgasse 29; AT- 1210 Wien Scheydgasse 29, 1210 AUT
Contact Name	Ms. Kim Villaluz

Quality	nola
Quoted Fibre Composition	2% AF, 16% CO, 10% PA, 33% PAN, 39% PES FR
Retailer	General

Test	Method	Sample	Result
Snagging Resistance - Rotating Chamber Method	BS 8479: 2008	G = Fuzzing	See Results

Tests marked (^) in this report have been performed by an approved 3rd party laboratory.
Tests marked (*) in this report are not included in our UKAS scope of accreditation.



Samantha Hurst
(Technician)

Snagging Resistance - Rotating Chamber Method BS 8479: 2008

Conditioning Parameters: 20°C±2°C & 65% rH±4% rH

Sample: G = Fuzzing

	Result	Requirement
2000 revs		
Specimen 1	4 - 5	
Specimen 2	4 - 5	
Specimen 3	4 - 5	
Specimen 4	4 - 5	
mean	4 - 5	
	Classification	
Specimen 1	C G	
Specimen 2	C G	
Specimen 3	C G	
Specimen 4	C G	
	Number of snags in each length category	
≤2 mm: short	0	
>2 mm but ≤5 mm: medium	0	
>5 mm: long	0	
Classification Key		
C - Indentations		
G - Other defects		

Overall Test Result: See Results

Uncertainty: 1/2 grade

Report Type	Issue Date	Revision Reason	Revision Description
Original	15-Jan-25	Complete Original Issue	N/A

The client acknowledges and agrees that any services provided and/or reports produced by Intertek are done so within the limits of the scope of work agreed pursuant to the client's specific instructions. This report relates specifically to the sample(s) tested that were drawn and delivered by the client or their nominated third party. Intertek does not make any representation or warranty for any bulk samples or certify the bulk samples received from the client. Furthermore, Intertek does not provide a warranty or verification on the sample(s) representing any specific goods, material and/or shipment and only relate to the sample(s) as received and tested. Intertek have aimed to conduct the review on a diligent and careful basis and we do not accept any liability to you for any loss arising out of or in connection with this report, in contract, tort, by statute or otherwise, except in the event of our gross negligence or willful misconduct. In no event, will the contents of any reports or any extracts, excerpts or parts of any reports be distributed or published without the prior written consent of Intertek in each instance. Only the client is authorized to permit copying or distribution of this report (and then only in its entirety). Any such third parties to whom this report may be circulated rely on the content of the report solely at their own risk.

The reported expanded uncertainty is based on a standard uncertainty multiplied by a coverage factor of $k = 2$, providing a level of confidence of approximately 95 %. Unless otherwise specified all compliance and pass/fail statements are binary simple acceptance based on the tolerance interval and, with the exception of graded methods, a test uncertainty ratio greater (TUR) than 4:1. For graded methods the TUR will drop to as low as 0.5:1 when the tolerance limits are within a grade division of the upper scale limit. The Uncertainty budgets are stated for each Test method, these are for reference and where a % value is stated it should be applied to the stated result, this % value is accurate at the acceptance limit, where results are significantly different to the acceptance limit the calculated uncertainty may be over or understated. Uncertainty should be carefully considered when results are on or close to Specification Limits / Requirements - in such cases it should be noted that the risk of false acceptance or rejection may be as high as 50%, for further information please refer to ILAC G8.